



DASH NO.	'A' SHAFT DIA.	'B' BORE DIA.	'C' GROOVE DIA.	'D' AXIAL LG.	'E' C'BORE DEPTH	'F' PIN LOC.	'G' PIN DIA.	O'RING PART NO.
-16	1.000	1.510	1.734	.500	.437	.057	3/32	-222
-18	1.125	1.635	1.859			.057	3/32	-223
-20	1.250	1.885	2.109			.075	1/8	-225
-22	1.375	2.010	2.234					-226
-24	1.500	2.135	2.359					-227
-26	1.625	2.260	2.484					-228
-28	1.750	2.385	2.609					-229
-30	1.875	2.510	2.734					-230
-32	2.000	2.635	2.859	.500	.437			-231
-34	2.125	2.760	2.984	.562	.500			-232
-36	2.250	2.885	3.109					-233
-38	2.375	3.010	3.234					-234
-40	2.500	3.135	3.359	.562	.500			-235
-42	2.625	3.260	3.484	.625	.562			-236
-44	2.750	3.385	3.609					-237
-46	2.875	3.510	3.734					-238
-48	3.000	3.635	3.859					-239
-50	3.125	3.760	3.984					-240
-52	3.250	3.885	4.109					-241
-54	3.375	4.010	4.234					-242
-56	3.500	4.135	4.359	.625	.562			-243
-58	3.625	4.260	4.484	.687	.625			-244
-60	3.750	4.510	4.734	.687	.625	.075	1/8	-246

BLOCK SEAT
GLAND CAVITY
DIMENSIONAL CHART

FLEX-A-SEAL, INC.
P.O. BOX 184/ 1 JACKSON ST.
ESSEX JUNCTION, VT 05453
(802) 878-8307

DRAWING NO.:

SK1408

SIZE

REV.

1

REV	ECN#	DATE	REV BY
1	965	6/13/01	D.D.D.

SCALE: NONE DRAWN BY: PN DATE: 4/22/98